

Series UTA - Universal Telephone Alerts

Description:

Wheelock Universal Indoor/Outdoor Telephone Alerts: UTA-1 and UTA-WH-VPS are loud attention getting electronic ringers designed for use in noisy locations or for wide area coverage. The UTA-1 operates off the telephone ringer voltage. The UTA-WH-VPS requires 115 VAC and telephone ring trigger voltage for activation of the strobe and ringer.

Features:

UTA-1 and UTA-WH-VPS

- Approvals Include: UL Standard 1950 approved
- ADA Compliant
- Choice of four selectable sound patterns: Horn, Bell, Vibrating Chime, Single Chime
- Choice of four operating voltages: 24VDC, 24VAC, 48VDC, 90Vrms/20-30Hz
- High output 109 dB piezo speaker
- Low current draw and REN
- Tamper resistant volume control
- Dip switch selectable
- Equipped with a weather resistant backbox for optional outdoor use with conduit-enclosed wiring
- Complies with: FCC part 68, CSA C22.2, IC C5-03

UTA-WH-VPS Universal Telephone Alert with Strobe

- Includes a high intensity 15 candela flashing strobe for visual signaling
- Equipped with a weather resistant backbox for optional outdoor use with conduit-enclosed wiring
- Requires 115 VAC power for strobe and piezo operation, and telephone ring trigger voltage for activation - Line cord purchased separately



Series UTA-WH-VPS



Series UTA-1

Applications:

Offices of all types
Manufacturing Plants
Machine shops
Factories
Construction sites
Shipping Yards
Processing Plants
Warehouses

Specification and Ordering Information

Model Number	Order Code	Description	Power Requirements
UTA-1	6338	Universal Telephone Alert	24 VDC, 24 VAC, 48 VDC, 90 VRMS/20-30Hz
UTA-WH-VPS	6348	Universal Telephone Alert w/ Strobe	Requires 115 VAC power for strobe and piezo operation, and telephone ring trigger voltage for activation via 24VDC, 24VAC, 48VDC, 90VRMS/20-30Hz (Line cord purchased separately)

Tone Volume Range and Description

Horn	82-109 dB	Broadband Horn
Bell	76-104 dB	1560 Hz Modulated (0.07 Sec. ON/Repeat)
Vibrating Chime	68-94 dB	700 Hz (1.0 Sec. Decay/Repeat)
Single Chime	68-94 dB	700 Hz (1.0 Sec. Decay)

Note: Not intended for wash down areas.

Model Number	Tones	dB @ 3 Feet (1 meter)				Ring Voltage Current Draw mA			REN
		48 VDC	24 VDC	24 VAC	90 VRMS 20 Hz	48 VDC	24 VDC	24 VAC	90 VRMS 20 Hz
UTA-1	Horn	107	108	105	104	26	30	46	1.6
	Bell	100	100	102	100	10	9	39	1.4
	Vibrating Chime	94	96	99	97	7	6	29	1.25
	Single Chime	94	96	100	96	6	6	34	1.25
UTA-WH-VPS	Horn	109	109	109	109	3	2.5	4	.6
	Bell	104	104	104	104	3	2.5	4	.6
	Vibrating Chime	94	94	94	94	3	2.5	4	.6
	Single Chime	94	94	94	94	3	2.5	4	.6
Voltage Range						36-60	20-30	20-30	40-130

02/04